

CAP EXTRUSION &
STANDARD COVER

GLASS (SEE NOTE)

SILICONE SEALANT

BACKER ROD

OPEN CELL
FOAM TAPE

80 DUROMETER
SETTING BLOCK
ONE @ EACH END

WEEP GROOVE

INTERNAL CONNECTOR
W/ 1/4" ϕ F.H.S.S. BOLT
(WELDED TO RAFTER)

FURLIN (2" EXTRUSION
SHOWN)

INTERNAL CONNECTOR W/
1/4" ϕ F.H.S.S. BOLTS
(IF APPLICABLE)

RAFTER TUBES (4" EXTRUSION
SHOWN) (WELD TOGETHER
IF APPLICABLE)

10 SEGMENTED PURLIN DETAIL

SCALE: 1/2" = 1'-0"

NOTE:

- 1 3/16" INSULATED GLAZING SHOWN (THICKNESS & TYPE PER ARCHITECT AND ENGINEER)
- FURLIN SIZE PER DESIGN CRITERIA.
- CONNECTION AT RAFTER JOINT MUST BE REVIEWED BY ENGINEER TO VERIFY LOADING OF RAFTERS.

EVERGREEN HOUSE

13645 N.E. 126th Place, Kirkland, WA 98034

(425) 821-1005 FAX (425) 823-5619

TYPICAL DETAILS

DRAWN BY: JJD

DRAWING NUMBER:

DATE: OCT. 11

T-10