

SILICONE SEALANT

CUSTOM ALUM. FLASHING (ONLY APPLICABLE IF REQUIRED BY SURROUNDING CONSTRUCTION)

ALUM. RIDGE FLASHING (Ø50)

WEEP GROOVE AS REQ'D

CAP EXTRUSION & STANDARD COVER

SILICONE SEALANT

BACKER ROD

OPEN CELL FOAM TAPE

GLASS (SEE NOTE)

INTERNAL CONNECTOR W/ 1/4" Ø S.S. BOLTS (WELDED TO END IR)

INTERNAL CONNECTOR W/ 1/4" Ø F.H.S.S. BOLTS (WELDED TO RAFTER)

1/4" CONTINUOUS ALUMINUM BEARING PLATE

RUBBER ISOLATION PAD

RIDGE TUBE (4" EXTRUSION SHOWN) (MODIFIED WITH BACK CUT-OUT)

BOLT SIZE PER ENGINEER

### 3A RIDGE DETAIL

SCALE: 1/2" = 1'-0"

#### NOTE:

- 1 3/16" INSULATED GLAZING SHOWN (THICKNESS & TYPE PER ARCHITECT AND ENGINEER)
- WALL CONSTRUCTION TO BE CAPABLE OF WITHSTANDING LOADS APPLIED BY SKYLIGHT.
- VARIABLE SLOPE

# EVERGREEN HOUSE

## TYPICAL DETAILS

DRAWN BY: JJD

DRAWING NUMBER:

DATE: OCT. 11

# T-3A

13645 N.E. 126th Place, Kirkland, WA 98034

(425) 821-1005 FAX (425) 823-5619